



**Processor**

Quad-core ARM® Cortex® A53 processor with a maximum frequency of 1.2GHz per core supporting 32 and 64bit computing

**Excellent graphics processing power**

HD video 720p@60fps  
HD video 1080p@30fps

**Wide range of application scenarios**

Applications in the communications, smart home, smart healthcare, Internet of Things (IOT) applications

**Support system diversification**

Android  
Linux  
Windows 10 IoT core

**Graphics**

Adreno™ 306 400MHz 3D graphics accelerator, PC-level graphics processing power

**Camera**

Support 13MP camera, support wavelet denoising, JPEG decoding and other hardware-level post-processing techniques.

**Compatibility**

Compatible with Mezzanine Board interface standard.  
Multiple Mezzanine boards (optional)

**Service**

Provide comprehensive quality assurance and technical support  
Mass production service

## Product Specification



CPU	Snapdragon 410E, Quad core
GPU	Qualcomm® Adreno™ 306
CPU Frequency	1.2GHz
Internal Memory	1GB/2GB LPDDR3 533MHz
Internal Storage	8GB/16GB eMMC 5.0
OS	Android 6.0, Linux based on Debian, Windows 10 IoT core
Bluetooth	4.0
Built-in WiFi	WLAN 802.11 b/g/n/ac 2.4GHz/5.0GHz Note: Android doesn't support WiFi 5GHz
WiFi Frequency Range	2.400~2.497GHz, 5.725 ~ 5.825 GHz
Ethernet port	RJ45 10/1000Mbps
GPS	Yes
USB Interface	2x USB 2.0 type A (host mode only), 1x USB 2.0 micro B (device mode only), support OTG
Micro SD Card Slot	1
Display	HDMI 1.3 – HDMI full-size type A connector (1080p HD @ 30 fps), 1x MIPI-DSI 4-lane, up to 720p 30fps or 1080p 30fps for optional display/touch
Expansion connector	1x Mezzanine boards 40 pin Low-Speed connector <ul style="list-style-type: none"> <li>• UART, SPI, I2S, I2C x2, GPIO x12, DC power</li> </ul> 1x Mezzanine boards 60 pin -Speed connector High <ul style="list-style-type: none"> <li>• 4L-MIPI DSI, USB, I2C x2, 2L+4L-MIPI CSI</li> </ul> Footprint for one optional 16-pin Analog expansion connector <ul style="list-style-type: none"> <li>• Headphone output, Class-D speaker driver output, Microphone input, FM RX Antenna</li> </ul>
Size (mm)	85 * 60*12mm
Operating Temp	-25°C to +85°C
Power	DC:+6.5V to +18V

**Geniatech**  
Seeing is believing

18<sup>th</sup> F, G.D.C Building, No.9 Gaoxin Middle 3<sup>rd</sup> Rd, Nanshan District, Shenzhen City, China  
TEL:+86-755-86028588 FAX:+86-755-26710210  
[www.geniatech.com](http://www.geniatech.com) E-mail:[sales@geniatech.com](mailto:sales@geniatech.com)