

# HD Video Capture U800 II

# Geniatech



U800 II full HD Video capture is 1080p 60fps capture with USB 3.0. It supports UVC and no need to install driver any more comparing with other captures. Moreover, it can be compatible with most third party media player, smoothly connecting with the mainstream broadcast platform which can transfer web broadcast, video conference and so on to Skype, Facebook Live, YouTube Live, LiveStream, UStream, Dacast, Wowza Cloud. Support Windows, Mac, Linux, Android and other main OS

- Driver Free plug and play
- Support Mac, Windows, Android, Linux OS
- Support HDMI input and microphone Input. Users can add any other audio into the video through microphone when video recording
- Support 4K 30fps HDMI input, and 1080P 60fps HDMI output. It can connect to large screen television, so users can watch high quality video on the big screen while capturing and broadcasting
- Strong system compatibility
- Compatible with most third-party mainstream media players



## Product Features

- USB3.0
- HDMI input
- HDMI Out Connecting Large Screen TV
- Microphone input, recording your voice commentary and video together
- Supported External device:Bluerey DVD,WiiU,Xbox 360,Xbox One,Ps4,HDMI PVR,Armarium..
- Scenario: video conference, Speech Recording, Tele-medicin, Stream media and so on.
- Maximum input resolution:4K@30fps
- Maximum recording resolution:1080P@60fps

## Product Applications

- Compatible with most third-party mainstream media players  
Adobe Flash Media Live Encoder (Windows, OS X), Real Producer Plus (Windows), QuickTime Broadcaster (OS X), QuickTime Player (OS X), Windows Media Encoder (Windows), Daum Potplayer (Windows, OS X), Xsplit Broadcaster (Windows, OS X), VLC (Windows, OS X, Linux), Wirecast (Windows, OS X), OBS Studio(Windows, OS X),OBS Broadcaster(Windows, Mac OS X), vMix(Windows), AMCAP, ...
- Support OS:Winddows 7/8/8.1/10,OSX 10.9 above,Linux,Android

## I/O Interface

USB output	1x USB3.0
Video/Audio input	1x HDMI 1x Microphone
Video/Audio ouput	1x HDMI

## Mechanical

Dimension	96 x 64 x 15mm (3.8" x 2.52" x 0.59")
Weight	55g
Environment	Operating Temp.0~50℃ Storage Temp.-20℃ to 60℃ Humidity:10 to 85%
Certification	CE/FCC